



CURRENT SIZES

4-1/2" (9.5 -15.1#)

STANDARD OFFERING

- P110 Type Flow Wet
 - 350°F
- LTC Box x Pin

OPTIONS

- Flow Wet Materials
 - Connections
- Connection Configurations
- Other sizes available upon request

INQUIRIES

KX Oil Tools Inc.
4809 – 76th Ave. SE
Calgary, Alberta,
Canada
T2C 2X1

email:
info@kxoiltools.com

web:
www.kxoiltools.com

Open Hole Packer

KX Oil Tools Open Hole Packer is a hydraulically actuated packer that is typically utilized to isolate in an open-hole completion. To activate, differential pressure from annulus to tubing is required to initiate the set. Subsequent additional pressure will allow the piston to travel axially, and complete the set of the element. Once the element is set, zonal isolation is achieved across the annulus, and stimulation or production operations can be completed.

APPLICATIONS

- Production
- Injection
- Stimulation

FEATURES, BENEFITS & ADVANTAGES

- KX shear pins eliminate inconsistencies in shear values, due to improper and inconsistent user installation
- Opening pressure can be field adjusted from the outside of the tool by removing or installing additional shear screw
- Integral mandrel for increased strength
- Extremely compact
- Torque through capable for field makeup to work string
- Full bore ID to match connections size and weight



KX Oil Tools
 — INC —