



CURRENT SIZES

4-1/2" (9.5 -15.1#)

STANDARD OFFERING

- P110 Type Flow Wet
 - 350°F
 - LTC Pin

OPTIONS

- Flow Wet Materials
 - Connection
- Connection Configuration
- Other sizes available upon request

INQUIRIES

KX Oil Tools Inc.
4809 – 76th Ave. SE
Calgary, Alberta,
Canada
T2C 2X1

email:
info@kxoiltools.com

web:
www.kxoiltools.com

Tri-Jay Shorty Tieback Receptacle

KX Oil Tools Tri-Jay Shorty Tieback Receptacle is utilized in conjunction with the Tri-Jay Shorty Seal Assembly. This product can be used to convey tubing, a lower completion, or set a liner in place.

The robust three lug jay design enables the lower completion to be hooked up on surface and installed to the desired depth. Once on depth, to release, hold right hand torque, pickup, and rotate to the right to come out of the jay.

This simple design is suitable for cemented liner systems, and strong enough to convey frac liners in place, and perform the stimulation program.

APPLICATIONS

- Production
- Injection
- Stimulation
- Cementing

FEATURES, BENEFITS & ADVANTAGES

- Matched tubing or liner internal diameter
- Robust three lug jay handles higher load and torque than a typical two lug system
- Enables hydraulic isolation from the work string to the liner

