



# Quarter Turn Double Grip Anchor

## CURRENT SIZES

- 4-1/2" (9.5 - 13.5#)
- 4-1/2" (13.5 - 15.1#)
- 5-1/2" (14.0 - 20.0#)
- 5-1/2" (20.0 - 23.0#)
- 5-1/2" (23.0 - 26.0#)
- 7" (17.0 - 26.0#)
- 7" (26.0 - 32.0#)

## STANDARD OFFERING

- Standard Mandrel
- API Connection
- Carbide Slips

## OPTIONS

- Big Bore Mandrel
- Connection Configurations
- Other sizes available upon request

The KX Oil Tools Quarter Turn Double Grip Anchor is a mechanically set double grip tubing anchor designed to be run in a wide range of well types. The double slip design allows the anchor to be set in neutral, tension or compression. The proven J-slot design allows for easy setting and releasing of the anchor. The KX Anchor is equipped with an adjustable secondary shear release and comes standard carbide upper and lower slips.

## ANCHOR OPERATION

The KX Anchor is run to depth, pick up on the tubing string and rotate the pipe ¼ turn at the tool. Set weight onto the lower slips and then pull 10,000lbs tension into the upper slips to confirm the anchor is set. Land tubing in required tension or compression.

To release the anchor set compression on the lower slips, rotate the pipe ¼ turn at the anchor and pick up. Additional tension may be required to unset the anchor.



## PRODUCT SPECIFICATIONS

CASING		HOLE SIZE	TOOL OD	TOOL ID	THREAD	PART #
SIZE	WEIGHT					
4-1/2"	9.5 - 13.5	3.920 - 4.090	3.750	1.94	2-3/8" EUE	100072
	13.5 - 15.1	3.826 - 3.920	3.650	1.94	2-3/8" EUE	100073
5-1/2"	14.0 - 20.0	4.778 - 5.012	4.625	2.38	2-7/8" EUE	100074
	20.0 - 23.0	4.670 - 4.788	4.500	2.38	2-7/8" EUE	100075
	23.0 - 26.0	4.548 - 4.670	4.406	2.38	2-7/8" EUE	100076
7"	17.0 - 26.0	6.276 - 6.538	6.000	2.50	2-7/8" EUE	100077
	26.0 - 32.0	6.094 - 6.276	5.875	2.50	2-7/8" EUE	100078
	17.0 - 26.0	6.276 - 6.538	6.000	3.00	3-1/2" EUE	100777
	26.0 - 32.0	6.094 - 6.278	5.875	3.00	3-1/2" EUE	100778

## INQUIRIES

**KX Oil Tools Inc.**  
**4809 - 76<sup>th</sup> Ave. SE**  
**Calgary, Alberta,**  
**Canada**  
**T2C 2X1**

email:  
[info@kxoiltools.com](mailto:info@kxoiltools.com)

web:  
[www.kxoiltools.com](http://www.kxoiltools.com)



**KX Oil Tools**  
**INC**