

# **CURRENT SIZES**

Variable Sizes Available

## STANDARD OFFERING

- L-80 Material
- 250F Temperature Rating
- LTC or BTC Connections
- 5000psi Pressure Rating

# **OPTIONS**

- 300F Temperature Rating
- Premium Connections Available
  - Premium Materials Available

#### **INQUIRIES**

KX Oil Tools Inc. 4809 – 76™ Ave. SE Calgary, Alberta, Canada T2C 2X1

email: info@kxoiltools.com

web: www.kxoiltools.com

# **Liner Indexing Joint**

KX Oil Tools Liner Indexing Joint is a device run in the casing or liner string to aid in the deployment of the casing to TD. The Liner Indexing Joint is typically run in conjunction with the KX Eccentric Nose Float Shoe, and allows for orientation of the Eccentric Nose Float Shoe without rotation of the entire liner or casing string. Once weight is set on the Liner Indexing Joint, upward movement of the string will cycle the internal mechanism, to rotate the lower section of the Indexing Joint.

## **APPLICATIONS**

- Primary Cementing
- Liner Deployment
- Casing Deployment

# **FEATURES, BENEFITS & ADVANTAGES**

- No rotation required at surface
- Tool ID Matches Casing/Liner ID
- Indexing Mechanism is Isolated from debris
- 5000psi Pressure Rating
- 300F Temperature Rating



