

STANDARD OFFERING

- 10,000psi Pressure Rated
 - KCL Dissolvable Plug

OPTIONS

- Caged Ball
- Drop Ball
- Bridge Plug
- Protective Coatings

KX Oil Tools Inc. 4809 – 76: Ave. SE Calgary, Alberta, Canada T2C 2X1

email: info@kxoiltools.com

web: www.kxoiltools.com

KX Neo Plug

KX Oil Tools "Neo Plug" is a high performance 10k pressure rated dissolvable frac or bridge plug that offers operators the ability to save on their completion costs by reducing the time needed to get the wellbore stimulated and then onto production. The KX Oil Tools Neo Plug can be easily configured to run as a drop ball frac plug, a caged ball frac plug, or bridge plug.

The KX Oil Tools Neo Plug establishes the industry standard in dissolvable elastomeric technology and provides superior sealing capability during pack off and during stimulation. The body and seal of the plug is completely dissolvable and eliminates the need for milling or drilling of the plug at a later date.

Patent Pending

APPLICATIONS

- Fracturing
- Isolation
- Stimulation

DISSOLUTION INFORMATION

Dissolution Time (days)						
Temp °C	Freshwater	0.1% KCL	1% KCL	3% KCL	8% KCL	15% KCL
20	0.00	0.00	0.00	0.00	0.00	532.2
45	0.00	223.6	69	28.3	11.6	9.8
60	0.00	98.1	14.8	7.0	4.8	4.4
75	0.00	19.5	7.8	5.0	3.7	2.9
90	0.00	17.8	4.6	3.5	2.2	2.0
Estimate 4-1/2" NEO Plug dissolution time verified through lab and plug construction testing.						

