



### Current sizes

- 4.500"
- 5.500"
- 7.000"

### standard offering

- 10K Pressure Rated
- 250° F Temperature Rated
  - NBR Elastomer

### options

- Elastomer Material
- Connection Configurations
- Other sizes available upon request

### INQUIRIES

KX Oil Tools Inc.  
4809 – 76<sup>th</sup> Ave. SE  
Calgary, Alberta, Canada  
T2C 2X1

email:  
info@kxoilttools.com

web:  
www.kxoilttools.com

## Ball Drop Cement Retainer

KX Oil Tools Ball Drop Cement Retainer allows operators to use proven Cement Retainer technology with the added versatility of being able to deploy individual or a group of drop balls to plug the perforations during the course of a cement squeeze. This will allow operators to ensure that cement is placed across all of the squeeze perforations increasing the likelihood of a successful cement job.

### Applications

- Targeted Perforation Cement Squeezes
- Remedial Cement Squeezes
- Stage Cement Squeezes

### Features, benefits, and advantages

- Can be run as Wireline or Mechanical Set
- Ball Drop Retainer can be easily drilled or milled
- Retainer is pressure competent once set
- Valve can be Opened and Closed with standard Stinger
- Valve closes automatically when Stinger is removed



Casing Size	Weight range	OD	Ball Size	Pressure Rating	Temp. Rating (NBR)
(inches)	(lb/ft)	(inch)	(inch)	(psi)	°F
4 1/2	9.5-15.1	3.593	0.625	10000	250
5 1/2	13.0-23.0	4.312	0.625	10000	250
7	17.0-35.0	5.680	0.875	10000	250



KX Oil Tools

INC